



PCB LAYOUT

Specifications:
 Electrical:
 Contact Resistance:30 milliohms MAX
 Dielectric Withstanding Voltage:500 V AC AT Sea Level
 Insulation Resistance:1000 MEGA ohms MIN

Mechanical:
 Mating Force:3.5 KG MAX
 Umating Force:0.7 KG MIN.

3	HOUSING	WHITE PBT	1	UL 94V-0
2	SHELL	BRASS	1	PLATED NI
1	TERMINAL	PHOSPHOR BRONZE	4	Plated Gold in Mating Area Thru on Solder Falls
NO.	PARTS	MATERIAL	QTY.	FINISHING

UNLESS OTHERWISE SPECIFIED		APPROVAL		DATE	
TOLERANCES		DRAWN	CUIQUANWEI	20070720	
U.S.	METRIC	CHECKED			
±.05	0.25	APPROVAL			
±.005	0.15	DRAWING FILE :			
ANGLES ±.00°	2.00°	TITLE		USB A/F 90° 单层 T型 外扣 短弹白胶	
		PART NO.			
		SIZE	DRAWING NO.		REV.
		A4			A
		SCALE	1 : 1	SHEET	1 OF 1

DIMENSIONS		ANGLE OF PROJECTION	
U.S. INCHES	METRIC (MM)		

3

4

2

B

↑

C

—

A