



Specification

MATERIAL:
 Insulator: High Temperature Thermoplastic, UL 94V-0
 Contact: Copper Alloy
 SHELL: SUS

PLATING:
 Contact: Plated 50u" Ni Over all Contact Au 1U
 Shell: Plated 50u" Ni Overall
 Plated 1u" Au Selective Contact Area

Electrical:
 Current Rating : 0.5A .
 Voltage Rating : 30V AC/DC
 Ambient Temperature Range : 20° C+60° C
 Storage Temperature Range : -40° C+85° C
 Ambient Humidity Range : 95% R. H. Max.
 Contact Resistance: 100m max. Ω
 Insulation Resistance: 1000M min./500VDC
 产品耐温温度: 280° C
 Mating Cycles: 1500Min Insertions

SIM pin assignment	
PIN#	Name
C1	VCC 供电电压
C2	RST 重置
C3	CLK 时钟
C5	GND 接地
C6	VPP 程序电压
C7	I/O 输入输出

UNLESS OTHERWISE SPECIFIED TOLERANCE				东莞市讯普电子科技有限公司	
UNIT:	DECIMAL	LINEAR	ANGLES		
mm	X.	±0.50	±5°		
	X.X	±0.25	±3°		
	X.XX	±0.12	±1°		
www.xunpudianzi.com					
DRAWN	Fros	2014/12/12	DRAWN NAME:		
CHECKED	Ron	2014/12/12	MICRO SIM CONNECTOR		
APPROVED	Albert	2014/12/12	PRODUCT NO.	SMC-202-6	
SCALE	3.2	SHEET	1/1	SIZE	A4