



# High Speed HDMI Cable with Ethernet, UHD 4K, Digital Video with Audio, In-Wall CL2-Rated (M/M), 10 ft. (3.05 m)

MODEL NUMBER: P569-010-CL2



#### **Highlights**

- Supports UHD resolutions up to 4K (4:4:4) for crystal-clear video
- Backward compatible with previous HDMI generations
- CL2-rated PVC cable jacket meets required standards for inwall installation
- Foil/braid shielding protects against EMI/RFI line noise that can distort or destroy data

# **System Requirements**

 HDMI video source and HDMI enabled TV / Monitor

#### **Package Includes**

 10-ft. High Speed HDMI Cable with Ethernet (v1.4), In-Wall CL2-Rated

#### **Features**

## 4K HDMI Cable Connects Home Theater or Digital Signage Audio/Video Components

This high-speed HDMI cable securely connects laptops, tablets, PCs, Blu-ray players, game consoles, Roku/Apple TV boxes, satellite/cable TV receivers and other devices with HDMI outputs to HDTVs, HD monitors, projectors or home theater receivers with HDMI inputs. The 4K P569-010-CL2 is backward compatible with all your existing HDMI devices.

## Transmits Crystal-Clear 4K Video with Digital Audio and 4:4:4 Color

The P569-010-CL2 supports Ultra HD resolutions up to 4K, as well as multi-channel audio and 4:4:4 chroma subsampling for top-level PC gaming or using your HDTV as a PC monitor. HDCP 2.2 compliance allows you to stream 4K Amazon and Netflix content with no complications. It also supports Ethernet, so no separate cable is needed to connect devices online.

## **Premium Construction for Superior Performance**

High-quality materials ensure outstanding performance throughout the 28 AWG cable's lifetime. The PVC jacket carries a CL2 rating, making it suitable for in-wall cable installation. Contacts and connectors are gold-plated to provide maximum conductivity and minimum data loss to guarantee a clear transmission free of interference. Foil and braid shielding ensures reliable, error-free signal quality and protection from EMI/RFI line noise that can distort or destroy data.

## 10 ft. Cable Lets You Design an Audio/Video Application to Your Specifications

This long HDMI cable allows you greater flexibility in placing your home theater or digital signage components. For instance, your Blu-ray player or media server may be concealed some distance from the connected display for security purposes.

# **Specifications**

| OVERVIEW     |               |
|--------------|---------------|
| UPC Code     | 037332188243  |
| Product Type | Passive Cable |





| Technology                     | НДМІ                    |  |
|--------------------------------|-------------------------|--|
| Cable Type                     | Passive                 |  |
| VIDEO                          |                         |  |
| Max Supported Video Resolution | 3840 x 2160 (4K) @ 30Hz |  |
| Max Supported Color Depth      | 48-bit Deep Color       |  |
| HDR Support                    | No                      |  |
| 3D Video Supported             | Yes                     |  |
| Chroma Sub Sampling            | 4:4:4                   |  |
| EDID Support                   | Yes                     |  |
| Signal Transmission            | Bidirectional           |  |
| AUDIO                          |                         |  |
| Audio Specification            | ARC                     |  |
| CONNECTIONS                    |                         |  |
| Side A - Connector 1           | HDMI (MALE)             |  |
| Side B - Connector 1           | HDMI (MALE)             |  |
| Connector Plating              | Gold                    |  |
| Contact Plating                | Gold                    |  |
| Connector Style                | Straight                |  |
| Latching or Gripping Connector | No                      |  |
| USER INTERFACE, ALERTS & CON   | ITROLS                  |  |
| LED Indicators                 | 0                       |  |
| PHYSICAL                       |                         |  |
| Color                          | Black                   |  |
| Material of Construction       | PVC                     |  |
| Cable Jacket Color             | Black                   |  |
| Connector Color                | Black                   |  |
| Cable Jacket Material          | PVC                     |  |
| Cable Jacket Rating            | CL2                     |  |
| Cable Outer Diameter (OD)      | 6.0 mm                  |  |
| Wire Gauge (AWG)               | 30                      |  |
| Cable Length (ft.)             | 10                      |  |
| Cable Length (m)               | 3.05                    |  |
| Cable Length (in.)             | 120                     |  |





| Ferrite Core                                    | No                           |  |
|---|------------------------------|--|
| Minimum Bend Radius                             | 30mm                         |  |
| Shipping Dimensions (hwd / in.)                 | 9.00 x 7.00 x 0.50           |  |
| Shipping Dimensions (hwd / cm)                  | 22.86 x 17.78 x 1.27         |  |
| Shipping Weight (lbs.)                          | 0.34                         |  |
| Shipping Weight (kg)                            | 0.15                         |  |
| ENVIRONMENTAL                                   |                              |  |
| Operating Temperature Range                     | 14° to 122°F (-10° to 50°C)  |  |
| Storage Temperature Range                       | 5° to 140°F (-15° to 60°C)   |  |
| Operating Humidity Range                        | 0% to 90% RH, Non-Condensing |  |
| Storage Humidity Range                          | 0% to 90% RH, Non-Condensing |  |
| COMMUNICATIONS                                  |                              |  |
| EDID Compatible                                 | Yes                          |  |
| Consumer Electronics Control (CEC)<br>Supported | Yes                          |  |
| FEATURES & SPECIFICATIONS                       |                              |  |
| EMI/RFI Line Noise Protection                   | No                           |  |
| MST Support                                     | No                           |  |
| Antibacterial                                   | No                           |  |
| IP68 Rated                                      | No                           |  |
| IP20 Rated                                      | No                           |  |
| Armored Cable                                   | No                           |  |
| Ethernet Support                                | Yes                          |  |
| Fire Rating                                     | CL2 Rated                    |  |
| HDCP Specification                              | 1.4; 2.2                     |  |
| STANDARDS & COMPLIANCE                          |                              |  |
| Product Compliance                              | RoHS; REACH                  |  |
| WARRANTY & SUPPORT                              |                              |  |
| Product Warranty Period<br>(Worldwide)          | Lifetime limited warranty    |  |





1000 Eaton Boulevard Cleveland, OH 44122 United States https://tripplite.eaton.com © 2024 Eaton. All Rights Reserved. Eaton is a registered trademark. All other trademarks are the property of their respective owners.