



4-Port Ultra-Slim Portable USB 3.x (5Gbps) Hub

MODEL NUMBER: U360-004-SLIM











Pocket-sized portable hub connects to the USB 3.0 port on your laptop, Ultrabook or computer to give you four external USB 3.0 ports.

Description

The U360-004-SLIM 4-Port Ultra-Slim Portable USB 3.0 SuperSpeed Hub's built-in USB cable connects to your laptop, Ultrabook™ or computer to expand the number of available USB 3.0 ports. Just plug and play with no drivers, software or external power supply needed. The bus-powered hub distributes necessary power to its four USB 3.0 ports through USB connection. When using a separate cable between the hub's USB Micro-B port and your device's USB port or a USB charger to draw additional power, the hub can provide up to 1.5A for fast charging of mobile devices.

The ultra-slim case measures 4.2 x 1.3 x 0.4 inches to fit easily into your pocket, backpack, briefcase or laptop bag to connect USB-enabled devices wherever you are. It supports USB 3.0 data transfer rates up to 5 Gbps—ten times faster than USB 2.0—and is backward compatible with USB 2.0 and USB 1.1 devices. All four ports support USB Battery Charging (BC) specification v1.2. The U360-004-SLIM is compatible with all Windows® and Mac® operating systems.

Features

Increases Your Computer's USB 3.0 Ports from 1 to 4

- Expands your laptop, Ultrabook or computer's USB 3.0 port to 4 external USB 3.0 ports
- Bus-powered unit requires no external power supply
- Plug and play—no drivers or software needed

Special Ultra-Slim Design

- Measures just 4.2 x 1.3 x 0.4 inches
- Fits easily into your pocket, backpack, briefcase or laptop bag
- Built-in cable is perfect for travel

Excellent Speed and Versatile Performance

- Supports USB 3.0 data transfer rates up to 5 Gbps—10 times faster than USB 2.0
- Ports can provide up to 1.5A when USB Micro-B port is connected to a second computer USB port or USB charger
- Supports USB Battery Charging (BC) specification v1.2
- Backward compatible with USB 2.0 and USB 1.1

Highlights

- Ultra-slim design fits easily into pocket or laptop bag
- Supports USB 3.0 data transfer rates up to 5 Gbps
- Plug and play—no drivers or software needed
- Backward compatible with USB 2.0 and USB 1.1
- USB ports can provide up to 1.5A for charging mobile devices

System Requirements

- Desktop computer, laptop or tablet with available USB 3.0 port
- Peripherals with available USB 3.0 port

Package Includes

 U360-004-SLIM 4-Port Ultra-Slim Portable USB 3.0 SuperSpeed Hub





Specifications

Product Type Hub Technology USB 3.x Host Connector USB A (MALE) VIDEO Number of Monitors Supported © Extended Mode No Mirror Mode No DATA Data Ports (4) USB A (FEMALE) Data Ports (4) USB A - USB 3.2 Gen 1 (5 Gbps) INPUT Bus Powered Yes Product Length (in.) 12 Product Length (cm.) 30.48 Product Length (m) 0.304 POWER POWER Power Source Type USB Power Consumption (Waits) 0.70 CONNECTIONS Number of Ports 4 Side B - Connector 1 (4) USB 3.0 A (FEMALE) Side B - Connector 2 MICRO-USB B (FEMALE)				
Product Type Hub Technology USB 3.x Host Connector USB A (MALE) VIDEO Number of Monitors Supported © Extended Mode No Mirror Mode No DATA Data Ports (4) USB A (FEMALE) Data Ports (4) USB A - USB 3.2 Gen 1 (5 Gbps) INPUT Bus Powered Yes Product Length (in.) 12 Product Length (cm.) 30.48 Product Length (m) 0.304 POWER POWER Power Source Type USB Power Consumption (Waits) 0.70 CONNECTIONS Number of Ports 4 Side B - Connector 1 (4) USB 3.0 A (FEMALE) Side B - Connector 2 MICRO-USB B (FEMALE)	OVERVIEW	OVERVIEW		
Technology USB 3.x Host Connector USB A (MALE) VIDEO Number of Monitors Supported 0 Extended Mode No Mirror Mode No DATA Data Ports (4) USB A (FEMALE) Data Ports (4) USB-A - USB 3.2 Gen 1 (5 Gbps) INPUT Bus Powered Yes Product Length (in.) 12 Product Length (cm.) 30.48 Product Length (cm.) 30.48 Product Length (m) 0.304 POWER POWER POWER Power Source Type USB Power Consumption (Watts) 0.70 CONNECTIONS Number of Ports 4 Side A - Connector 1 USB 3.0 A (MALE) Side B - Connector 2 MICRO-USB B (FEMALE)	UPC Code	037332199270		
Number of Monitors Supported 0	Product Type	Hub		
VIDEO Number of Monitors Supported 0 Extended Mode No Mirror Mode No DATA Data Ports (4) USB A (FEMALE) Data Ports Details (4) USB-A - USB 3.2 Gen 1 (5 Gbps) INPUT Bus Powered Yes Product Length (in.) 12 Product Length (em.) 30.48 Product Length (m) 0.304 POWER Power Source Type USB CONNECTIONS Number of Ports 4 Side A - Connector 1 USB 3.0 A (MALE) Side B - Connector 2 MICRO-USB B (FEMALE)	Technology	USB 3.x		
Number of Monitors Supported 0 Extended Mode No Mirror Mode No DATA DATA Data Ports (4) USB A (FEMALE) Data Ports Details (4) USB-A - USB 3.2 Gen 1 (5 Gbps) INPUT Bus Powered Yes Product Length (in.) 12 Product Length (cm.) 30.48 Product Length (in.) 1 Product Length (in.) 0.304 Power Power Source Type USB Power Consumption (Watts) 0.70 CONNECTIONS Number of Ports 4 Side A - Connector 1 USB 3.0 A (MALE) Side B - Connector 2 MICRO-USB B (FEMALE)	Host Connector	USB A (MALE)		
Extended Mode No Mirror Mode No DATA Data Ports (4) USB A (FEMALE) Data Ports Details (4) USB-A - USB 3.2 Gen 1 (6 Gbps) INPUT Bus Powered Yes Product Length (in.) 12 Product Length (cm.) 30.48 Product Length (m) 0.304 POWER Power Source Type USB Power Consumption (Watts) 0.70 CONNECTIONS Number of Ports 4 Side A - Connector 1 USB 3.0 A (MALE) Side B - Connector 2 MICRO-USB B (FEMALE)	VIDEO			
Mirror Mode No DATA Data Ports (4) USB A (FEMALE) Data Ports Details (4) USB A - USB 3.2 Gen 1 (5 Gbps) INPUT Bus Powered Yes Product Length (in.) 12 Product Length (cm.) 30.48 Product Length (in.) 1 Product Length (in.) 1 1 Product Length (in.) 1 1 1 1 1 1 1	Number of Monitors Supported	0		
DATA Data Ports (4) USB A (FEMALE) Data Ports Details (4) USB-A - USB 3.2 Gen 1 (5 Gbps) INPUT Bus Powered Yes Product Length (in.) 12 Product Length (cm.) 30.48 Product Length (m) 0.304 POWER Power Source Type USB Power Consumption (Watts) 0.70 CONNECTIONS Number of Ports 4 Side A - Connector 1 USB 3.0 A (MALE) Side B - Connector 2 MICRO-USB B (FEMALE)	Extended Mode	No		
Data Ports (4) USB A (FEMALE) Data Ports Details (4) USB-A - USB 3.2 Gen 1 (5 Gbps) INPUT Bus Powered Yes Product Length (in.) 12 Product Length (em.) 30.48 Product Length (ft.) 1 Product Length (m) 0.304 POWER Power Source Type USB Power Consumption (Watts) 0.70 CONNECTIONS Number of Ports 4 Side A - Connector 1 USB 3.0 A (MALE) Side B - Connector 1 (4) USB 3.0 A (FEMALE) Side B - Connector 2 MICRO-USB B (FEMALE)	Mirror Mode	No		
Data Ports Details (4) USB-A - USB 3.2 Gen 1 (5 Gbps)	DATA			
NPUT Sus Powered Yes Yes Product Length (in.) 12 Product Length (cm.) 30.48 Product Length (ft.) 1 Product Length (m) 0.304 Product Length (m) Product	Data Ports	(4) USB A (FEMALE)		
Bus Powered Yes Product Length (in.) 12 Product Length (cm.) 30.48 Product Length (ft.) 1 Product Length (m) 0.304 Power Nource Type Power Consumption (Watts) 0.70 CONNECTIONS Number of Ports 4 Side A - Connector 1 USB 3.0 A (MALE) Side B - Connector 2 MICRO-USB B (FEMALE)	Data Ports Details	(4) USB-A - USB 3.2 Gen 1 (5 Gbps)		
Product Length (in.) 12 Product Length (cm.) 30.48 Product Length (ft.) 1 Product Length (m) 0.304 Power Source Type Power Consumption (Watts) 0.70 CONNECTIONS Number of Ports 4 Side A - Connector 1 USB 3.0 A (MALE) Side B - Connector 2 MICRO-USB B (FEMALE)	INPUT			
Product Length (cm.) 30.48 Product Length (ft.) 1 Product Length (m) 0.304 Power Source Type Power Source Type USB Power Consumption (Watts) 0.70 CONNECTIONS Number of Ports 4 Side A - Connector 1 USB 3.0 A (MALE) Side B - Connector 1 (4) USB 3.0 A (FEMALE) Side B - Connector 2 MICRO-USB B (FEMALE)	Bus Powered	Yes		
Product Length (ft.) 1 Product Length (m) 0.304 POWER Power Source Type USB Power Consumption (Watts) 0.70 CONNECTIONS Number of Ports 4 Side A - Connector 1 USB 3.0 A (MALE) Side B - Connector 1 (4) USB 3.0 A (FEMALE) Side B - Connector 2 MICRO-USB B (FEMALE)	Product Length (in.)	12		
Product Length (m) 0.304 POWER USB Power Source Type USB Power Consumption (Watts) 0.70 CONNECTIONS Number of Ports 4 Side A - Connector 1 USB 3.0 A (MALE) Side B - Connector 1 (4) USB 3.0 A (FEMALE) Side B - Connector 2 MICRO-USB B (FEMALE)	Product Length (cm.)	30.48		
Power Source Type USB Power Consumption (Watts) 0.70 CONNECTIONS Number of Ports 4 Side A - Connector 1 USB 3.0 A (MALE) Side B - Connector 1 (4) USB 3.0 A (FEMALE) Side B - Connector 2 MICRO-USB B (FEMALE)	Product Length (ft.)	1		
Power Source Type USB Power Consumption (Watts) 0.70 CONNECTIONS Number of Ports 4 Side A - Connector 1 USB 3.0 A (MALE) Side B - Connector 2 MICRO-USB B (FEMALE)	Product Length (m)	0.304		
Power Consumption (Watts) CONNECTIONS Number of Ports 4 Side A - Connector 1 USB 3.0 A (MALE) Side B - Connector 2 MICRO-USB B (FEMALE)	POWER			
CONNECTIONS Number of Ports 4 Side A - Connector 1 USB 3.0 A (MALE) Side B - Connector 1 (4) USB 3.0 A (FEMALE) Side B - Connector 2 MICRO-USB B (FEMALE)	Power Source Type	USB		
Number of Ports 4 Side A - Connector 1 USB 3.0 A (MALE) Side B - Connector 1 (4) USB 3.0 A (FEMALE) Side B - Connector 2 MICRO-USB B (FEMALE)	Power Consumption (Watts)	0.70		
Side A - Connector 1 USB 3.0 A (MALE) Side B - Connector 1 (4) USB 3.0 A (FEMALE) Side B - Connector 2 MICRO-USB B (FEMALE)	CONNECTIONS			
Side B - Connector 1 (4) USB 3.0 A (FEMALE) Side B - Connector 2 MICRO-USB B (FEMALE)	Number of Ports	4		
Side B - Connector 2 MICRO-USB B (FEMALE)	Side A - Connector 1	USB 3.0 A (MALE)		
	Side B - Connector 1	(4) USB 3.0 A (FEMALE)		
Connector Plating Nickel	Side B - Connector 2	MICRO-USB B (FEMALE)		
Tributor running Tributor	Connector Plating	Nickel		
USER INTERFACE, ALERTS & CONTROLS				
LED Indicators White (Connection to Power)	LED Indicators	White (Connection to Power)		





CHARGING		
Charging Ports	USB-A: 5V 1.5A (7.5W)	
Charging Ports / Amps	(4) 1.5A	
PHYSICAL		
Color	Black	
Material of Construction	ABS	
Cable Jacket Material	TPE	
Cable Jacket Rating	VW-1	
Shipping Dimensions (hwd / in.)	0.70 x 5.60 x 2.40	
Shipping Dimensions (hwd / cm)	1.78 x 14.22 x 6.10	
Shipping Weight (lbs.)	0.15	
Shipping Weight (kg)	0.07	
Unit Dimensions (hwd / in.)	0.000 x 0.000 x 0.000	
Unit Packaging Type	Вох	
Unit Weight (lbs.)	0.09	
Unit Weight (kg)	0.04	
ENVIRONMENTAL		
Operating Temperature Range	-4° to 158°F (-20° to 70°C)	
Storage Temperature Range	-4° to 185°F (-20° to 85°C)	
Relative Humidity	20% to 80% RH, Non-Condensing	
BTUs	2.4 BTU/Hr	
Power Provided to Connected Device(s)	5V 1.5A (7.5W) Output per USB Port	
FEATURES & SPECIFICATIONS		
USB Hub Ports	Yes	
Number of USB Hub Ports	4	
USB Specification	USB 3.0 (up to 5 Gbps); USB 3.1 Gen 1 (up to 5 Gbps); USB 3.2 Gen 1 (up to 5 Gbps)	
Driver Required	No	
STANDARDS & COMPLIANCE		
TAA Compliant Option	N	
Product Compliance	RoHS; CE (Europe); REACH; FCC (USA)	
WARRANTY & SUPPORT		





Product Warranty Period (Worldwide)	3-year limited warranty
--	-------------------------

1000 Eaton Boulevard Cleveland, OH 44122 United States https://tripplite.eaton.com © 2024 Eaton. All Rights Reserved. Eaton is a registered trademark. All other trademarks are the property of their respective owners.