

NetCommander PS2 Server Interface Unit (SIU)

MODEL NUMBER: B078-101-PS2



Features

- Needed to connect a PS/2 Server to a B070 / B072-Series NetCommander KVM switch via Cat5e cable
- Eliminates the need for thicker, heavier KVM cables
- Compact, lightweight design
- Plug and Play; no software required
- No power supply required
- Allows a Server/CPU to be located up to 100-ft. (30.5 m) away from the KVM switch
- To convert DisplayPort or HDMI computers to VGA, use adapters P134-06N-VGA-V2 or P131-06N

Highlights

- Needed to connect a PS/2 Server to a B070 / B072-Series NetCommander KVM switch via Cat5e cable
- Easy to install; no software needed
- No power supply needed
- Allows a recommended maximum distance of 100-ft. (30.5 m) from KVM to Server via Cat5e cable
- Compact and lightweight design

System Requirements

- Server or CPU with a HD15 port and (2) PS/2 type connections
- A B070 / B072-Series NetCommander Cat5 KVM Switch
- Cat5e/6 cable; up to 100-ft. (30.5 m)
- To convert DisplayPort or HDMI computers to VGA, use adapters P134-06N-VGA-V2 or P131-06N

Package Includes

- (x1) B078-101-PS2 PS/2 Server Interface Unit (SIU)

Specifications

| OVERVIEW | |
|----------------------|-------------------------|
| UPC Code | 037332148438 |
| Accessory Type | Server Interface Unit |
| Technology | Cat5/5e; PS/2; VGA/SVGA |
| Accessory Class | KVM Switch Accessories |
| INPUT | |
| Bus Powered | Yes |
| Product Length (ft.) | 1.2 |
| CONNECTIONS | |
| Side A - Connector 1 | HD15 (MALE) |
| Side A - Connector 2 | (2) MINI DIN-6 (FEMALE) |



Powering Business Worldwide



| | |
|--|---|
| Side B - Connector 1 | RJ45 (FEMALE) |
| Computer Keyboard and Mouse Interface | PS/2 |
| Computer Monitor Interface | VGA |
| USER INTERFACE, ALERTS & CONTROLS | |
| LED Indicators | GREEN (RECEIVING POWER); ORANGE (SELECTED AS ACTIVE PORT) |
| PHYSICAL | |
| Color | Gray |
| Material of Construction | ABS |
| Shipping Dimensions (hwd / in.) | 1.10 x 5.12 x 5.90 |
| Shipping Dimensions (hwd / cm) | 2.79 x 13.00 x 14.99 |
| Shipping Weight (lbs.) | 0.24 |
| Shipping Weight (kg) | 0.11 |
| Unit Weight (lbs.) | 0.22 |
| Unit Weight (kg) | 0.10 |
| ENVIRONMENTAL | |
| Operating Temperature Range | -4° to 158°F (-20° to 70°C) |
| Storage Temperature Range | -4° to 158°F (-20° to 70°C) |
| FEATURES & SPECIFICATIONS | |
| IP68 Rated | No |
| IP20 Rated | No |
| Driver Required | No |
| Recommended Category Cable | N105 - SERIES CAT5E SHIELDED CABLES |
| STANDARDS & COMPLIANCE | |
| Product Certifications | EN 55022; EN 55024 |
| Product Compliance | RoHS; CE (Europe); REACH; FCC (USA) |
| WARRANTY & SUPPORT | |
| Product Warranty Period (Worldwide) | 3-year limited warranty |