

## 4-Port Desktop KVM Switch (USB)

MODEL NUMBER: B006-VU4-R



### Description

Tripp Lite's 4-port Desktop USB KVM Switch is the optimal solution for controlling up to 4 USB computers from one VGA monitor and USB keyboard/mouse. Manually switch between connected computers using pushbuttons or hotkey controls; or, monitor connected computers automatically via Auto Scan Mode. The B006-VU4-R is operating system independent, and works with all computers that have an available VGA and USB port. It supports video resolutions up to 2048 x 1536, and features a compact design that does not require software or complicated set-up procedures. Constructed of heavy-duty steel housing. Order P758 Cables separately.

### Features

- Control up to 4 USB computers from a single VGA monitor and USB keyboard/mouse
- Order P758 Cables separately
- Port LEDs illuminate Dim Orange to indicate a computer is connected, and Bright Orange to indicate it is the selected port
- Supports video resolutions up to 2048 x 1536, DDC2B
- No software or complicated set-up procedures required
- Manually switch between connected computers via front panel pushbuttons or hotkey commands
- Automatically monitor connected computers via Auto Scan Mode
- Compatible with all major operating systems
- Compatible with most mice; including scroll mice
- Constructed of heavy-duty steel housing

### Highlights

- Control up to 4 USB computers from a single VGA monitor and USB keyboard/mouse
- Switch between connected computers via pushbuttons or hotkey commands
- Auto Scan Mode allows monitoring of connected computers without manually switching between them
- Compatible with all major operating systems
- Supports video resolutions up to 2048 x 1536, DDC2B

### Package Includes

- B006-VU4-R 4-port USB KVM Switch
- External Power Supply with NEMA 1-15P Plug (Input: 100-240V, 50/60Hz, 0.5A / Output: 5.3V, 2.4A )
- Owner's manual

## Specifications

| OVERVIEW   |              |
|------------|--------------|
| UPC Code   | 037332152947 |
| Console    | No           |
| Max CPU    | 4            |
| Technology | VGA/SVGA     |



Powering Business Worldwide

**TRIPP-LITE**  
by **EAT•N**

| VIDEO                                     |                           |
|-------------------------------------------|---------------------------|
| Max Supported Video Resolution            | 2048 X 1536, DDC2B        |
| INPUT                                     |                           |
| AC Power Adapter Plug(s)                  | NEMA 1-15P North America  |
| AC Power Adapter Input Specs (V / Hz / A) | 100-240V / 50/60Hz / 0.5A |
| AC Power Adapter Output Specs (V / A)     | 5.3V / 2.4A               |
| AC Power Adapter Cord Length (ft.)        | 5                         |
| AC Power Adapter Cord Length (m)          | 1.5                       |
| POWER                                     |                           |
| Power Source Type                         | AC Adapter                |
| CONNECTIONS                               |                           |
| Number of Ports                           | 4                         |
| PC/Server Connections                     | USB; VGA                  |
| Side A - Connector 1                      | (4) HD15 (MALE)           |
| Side A - Connector 2                      | (4) USB B (FEMALE)        |
| Side B - Connector 1                      | (1) HD15 (FEMALE)         |
| Side B - Connector 2                      | (2) USB A (FEMALE)        |
| Computer Keyboard and Mouse Interface     | USB                       |
| Computer Monitor Interface                | VGA                       |
| Console Keyboard and Mouse Interface      | USB                       |
| Console Monitor Interface                 | VGA                       |
| USER INTERFACE, ALERTS & CONTROLS         |                           |
| LED Indicators                            | Online Selected (Orange)  |
| PHYSICAL                                  |                           |
| LCD Monitor (cm)                          | Not Applicable            |
| Shipping Dimensions (hwd / in.)           | 3.50 x 9.80 x 8.70        |
| Shipping Dimensions (hwd / cm)            | 8.89 x 24.89 x 22.10      |
| Shipping Weight (lbs.)                    | 2.20                      |
| Shipping Weight (kg)                      | 1.00                      |
| Unit Dimensions (hwd / in.)               | 1.700 x 7.900 x 2.900     |
| Unit Dimensions (hwd / cm)                | 4.32 x 20.07 x 7.37       |



Powering Business Worldwide



|                                      |                                   |
|--------------------------------------|-----------------------------------|
| Unit Weight (lbs.)                   | 1.50                              |
| Unit Weight (kg)                     | 0.68                              |
| <b>ENVIRONMENTAL</b>                 |                                   |
| BTUs                                 | 7.1694 BTU/Hr                     |
| <b>COMMUNICATIONS</b>                |                                   |
| Port Control                         | Push Buttons, Hotkeys             |
| IP Remote Access                     | No                                |
| <b>FEATURES &amp; SPECIFICATIONS</b> |                                   |
| USB Specification                    | USB 2.0 (up to 480 Mbps)          |
| NIAP-Certified Secure                | No                                |
| Number of Users                      | 1                                 |
| Autoscan (Y,N)                       | Y                                 |
| Autoscan Duration                    | 11 TO 99 SECONDS; USER-DEFINEABLE |
| <b>WARRANTY &amp; SUPPORT</b>        |                                   |
| Product Warranty Period (Worldwide)  | 3-year limited warranty           |

1000 Eaton Boulevard  
Cleveland, OH 44122  
United States  
<https://tripplite.eaton.com>

© 2026 Eaton. All Rights Reserved.  
Eaton is a registered trademark. All other trademarks  
are the property of their respective owners.